

## Description

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable (Screening Class B)

Coaxial Cables

CAVEL®

since 1968

## Data Sheet

SAT703B

Ø	1,13	4,80	4,90	5,30	6,60
	(Cu)	(PEG)	(Al/Pet/Al)	(CuSn)	(PVC)

## Class CPR acc. to UE 305/2011 (DoP)

E<sub>ca</sub>

The cable can be used in the field of application of the Construction Product Regulation (DoP) UE nr. 305/2011 for the class of performance specified on the related product label.

## Standards

EN 50117-2-4

## Fire-Resistance Rating

EN50575

## Construction data

Inner conductor of plain copper	(Cu)	Ø 1,13 ± 0,02	mm
Dielectric of physical foam polyethylene	(PEG)	Ø 4,80 ± 0,10	mm
Aluminium/Polyester/Aluminium tape longitudinally overlapped	(Al/Pet/Al)		
Water repellent sealing (dielectric)	(Jelly1)		
Braid of tinned copper wires	(CuSn)		
Braid optical coverage (IEC 96-1)		45	%
Diameter over Braid		Ø 5,30	mm
Outer sheath of Polyvinylchloride - white (PVC) - lead-free	(PVC)	Ø 6,60 ± 0,10	mm

Printed each meter by blue ink-jet :

**CAVEL SAT 703 B MADE IN ITALY 75 Ohm Euroclass Eca EN50117-2-4 CEI-UNEL 36762 C-4 (U0 = 400V) gggaa(n) m**

(ss=week, aa=year) (m=meter marking)

## Physical data

Weight of copper conductors	14,45	kg/km
Total weight of cable	39,53	kg/km
Minimum bending radius (single/repeated bending)	35/70	mm
Maximum cable pulling strength	150	N
Minimum installation temperature	-5	°C
Operating temperature	-40 / +80	°C

## Electrical data

Characteristic impedance	200 MHz	75 ± 3	Ohm
Capacitance (@1kHz)		52 ± 2	pF/m
Velocity Ratio		85 %	
Inner conductor resistance		18	Ohm/km
Outer conductor resistance		22	Ohm/km
Loop resistance		40	Ohm/km
Sheat Insulation voltage (spark test)		3	kV

## ITALIANA CONDUTTORI s.r.l.

Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212

## Date

29/02/2016

## Responsible

Alberto Scardovi

**Description**

Indoor drop coaxial cable - 75 Ohm  
 Indoor installation cable (Screening Class B)



Data Sheet


**SAT703B**

Maximum current (Ieff)		8	A
Structural return loss (SRL)			
5 - 470 MHz	>30 dB		
470 - 1000 MHz	>28 dB		
1000 - 2000 MHz	>26 dB		
2000 - 3000 MHz	>22 dB		
Screening Attenuation (SA)	SA-Class B	Shield Transfer Impedance (Zt)	Zt-Class C
30 - 1000 MHz	> 80 dB	5 - 30 MHz	< 23 mOhm/m
1000 - 2000 MHz	>80 dB		
2000 - 3000 MHz	>65 dB		

Attenuation (at 20°C )

Frequency [MHz]	Attenuation [dB/100m]	Frequency [MHz]	Attenuation [dB/100m]
5	1,60	862	17,10
10	2,10	1000	18,50
30	3,20	1750	24,90
50	4,10	2150	27,90
200	7,90	2400	29,60
300	9,80	3000	33,40
470	12,40		

**Attenuazione di schermatura / Screening Attenuation**  
**Cavo classe B / B Class Cable**  
 Cavo tipo / Cable type: SAT703B



**Connectors**

**BNCC703** Series BNC Compression, BNC Compression, for OUTDOOR installation, nitin-plated brass - 35,0 mm x 14,0 mm

**ITALIANA CONDUTTORI s.r.l.**

Viale Zanotti 90 I - 27027 Gropello Cairoli  
 Tel +39-382.815150 Fax +39-0382.814212

Date

29/02/2016

Responsible

Alberto Scardovi

**Description**

Indoor drop coaxial cable - 75 Ohm

Indoor installation cable (Screening Class B)

**Data Sheet****SAT703B**↑↑↑ **Connectors**

<b>F703</b>	Series F Crimp, F Crimp, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
<b>F90</b>	Series F Crimp, F Crimp, for INDOOR installation
<b>FA703</b>	Series F Twist-On, F Twist-On, for INDOOR installation, nitin-plated brass - 21,0 mm x 12,0 mm
<b>FC7.0QM</b>	Series F Compression, Quick Mount, for OUTDOOR installation
<b>FC703</b>	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass - 30,0 mm x 12,0 mm
<b>FCEM7.0C</b>	Series F Compression, F Compression, for OUTDOOR installation, nitin-plated brass
<b>FCPO5.1C</b>	Series F Compression, Ø 5,1 Push-On, for OUTDOOR installation, nitin-plated brass
<b>FR703</b>	Series F Crimp, F crimp, "Rapid", for INDOOR installation
<b>IECF5.1C</b>	Series IEC (toolless), female, no tool, for INDOOR installation
<b>IECF90C</b>	Series IEC (toolless), Ø 5,1 90° female, for INDOOR installation
<b>IECF703</b>	Series IEC Compression, female, no tool, for OUTDOOR installation
<b>IECM5.1C</b>	Series IEC (toolless), male, no tool, for INDOOR installation
<b>IECM90C</b>	Series IEC (toolless), Ø 5,1 90° male, for INDOOR installation
<b>IECMC703</b>	Series IEC Compression, male, for OUTDOOR installation

**ITALIANA CONDUTTORI s.r.l.**Viale Zanotti 90 I - 27027 Gropello Cairoli  
Tel +39-382.815150 Fax +39-0382.814212**Date****29/02/2016****Responsible****Alberto Scardovi**